

APP CRS 154°	Rwy Ldg 9001
	TDZE 43
	Apt Elev 46

RNAV (RNP) Z RWY 15




CHARLESTON AFB/INTL (CHS)

▼ For uncompensated Baro-VNAV systems, procedure NA below -5°C (23°F) or above 54°C (130°F). GPS required. For inop ALSF, increase RNP 0.11 all Cats visibility to RVR 4500 and RNP 0.30 all Cats visibility to RVR 6000.




MISSED APPROACH: Climb to 3000 on track 154° to SHRMP and hold.


D-ATIS 124.75	CHARLESTON APP CON 120.7 306.925	CHARLESTON TOWER 126.0 239.0	GND CON 121.9 348.6
-------------------------	--	--	-------------------------------



ELEV 46	TDZE 43
---------	---------



TDZL/RCLS Rwy 15
REIL Rwy 3 and 21
HIRL Rwy 3-21 and 15-33



GP 3.00° TCH 50	See planview for multiple IF locations.			3000 ↑ tr 154°	SHRMP
	3.2 NM				
CATEGORY	A	B	C	D	
RNP 0.11 DA		315/24	272 (300-½)		
RNP 0.30 DA		428/45	385 (400-¾)		

AUTHORIZATION REQUIRED

SE-2, 11 JUN 2026 to 09 JUL 2026

SE-2, 11 JUN 2026 to 09 JUL 2026