




WAAS CH <b>40006</b> <b>W18A</b>	APP CRS <b>176°</b>	Rwy Ldg TDZE Apt Elev	<b>9001</b> <b>900</b> <b>901</b>
--	------------------------	-----------------------------	---

# RNAV (GPS) RWY 18

HECTOR INTL (FAR)

RNP APCH.	<p><b>⚠</b> For inoperative MALS, increase LPV Cat E visibility to RVR 4000 and LNAV/VNAV Cat E and LNAV Cat D and E to RVR 6000. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). #RVR 1800 authorized with use of FD or AP or HUD to DA.</p>	MALS 	MISSED APPROACH: Climb to 3500 direct KOBME and hold.
-----------	--	----------	--

ATIS <b>124.5 379.2</b>	FARGO APP CON <b>120.4 377.15</b>	FARGO TOWER <b>133.8 290.4</b>	GND CON <b>121.9 348.6</b>
----------------------------	--------------------------------------	-----------------------------------	-------------------------------



CATEGORY	A	B	C	D	E
LPV DA#		1100/24	200 (200-½)		
LNAV/VNAV DA		1272/40	372 (400-¾)		
LNAV MDA	1260/24	360 (400-½)		1260/50	360 (400-1)
CIRCLING	1380-1	479 (500-1)	1520-1¾ 619 (700-1¾)	1620-2¼ 719 (800-2¼)	1620-2½ 719 (700-2½)

NC-1, 11 JUN 2026 to 09 JUL 2026

NC-1, 11 JUN 2026 to 09 JUL 2026