RNAV (GPS) RWY 36C

FREDERICK W SMITH INTL/MEMPHIS (MEM)

WAAS CH 40407 W36B	APP CRS 360°	Rwy Ldg 10715 / TDZE 341 / Apt Elev 341

RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Simultaneous approach authorized. For inop ALS increase LPV all Cats visibility to RVR 5000, increase LNAV Cat D visibility to RVR 6000. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations.

ALSF-2

MISSED APPROACH: Climb to 3000 direct LAURI and hold.

MEMPHIS APP CON		
119.1	291.6	(176°-355°)
125.8	338.3	(356°-175°)

MEMPHIS TOWER		
(Rwy 9-27)	118.3	257.8
(Rwys 18C-36C, 18L-36R)	119.7	257.8
(Rwy 18R-36L)	128.425	257.8

GND CON		
(Rwy 9-27)	121.0	379.2
(Rwys 18C-36C, 18L-36R)	121.9	379.2
(Rwy 18R-36L)	121.65	379.2

D-ATIS 127.75

MISSED APCH FIX





CATEGORY	A	B	C	D
LPV DA	665/24 324 (400-½)			
LNAV/VNAV DA	765/50 424 (500-1)			
LNAV MDA	760/24 419 (500-½)		760/40 419 (500-¾)	760/50 419 (500-1)
CIRCLING	940-1 599 (600-1)		940-1½ 599 (600-1½)	1020-2¼ 679 (700-2¼)

ELEV 341 D TDZE 341



SE-1, 11 JUN 2026 to 09 JUL 2026
SE-1, 11 JUN 2026 to 09 JUL 2026