

LOC/DME I-EZA	APP CRS	Rwy Ldg	4R 8809	4L 8459
108.7	039°	TDZE	11	10
Chan 24		Apt Elev	17	17

# ILS or LOC RWY 4R




NEWARK LIBERTY INTL (EWR)

RNP APCH - GPS. RADAR required.

When Circling to Rwy 29 at night, operational VGSI required, remain on or above VGSI glidepath until threshold. For inop ALS, increase Sidestep 4L Cat C visibility to 1½ SM.

4R ALSF-2	4L MALS	MISSED APPROACH: (Do not exceed 210K until NEBTE) Climb to 560 then climbing right turn to 2000 direct TYNIE and left turn on track 015° to NEBTE, cross NEBTE at or below 2000 then climbing left turn to 3000 on track 313° to FLYRS and hold, continue climb-in-hold to 3000.
-----------	---------	--

D-ATIS	NEWARK APP CON	NEWARK TOWER	GND CON
115.7 134.825	128.55 379.9	118.3 257.6	121.8



CATEGORY	A	B	C	D
S-ILS 4R	211/18 200 (200-½)			
S-LOC 4R	600/24	589 (600-½)	600-1¼	589 (600-1¼)
SIDESTEP RWY 4L	600/55	590 (600-1)	600-1¼	600-1½
			590 (600-1¼)	590 (600-1½)
CIRCLING	760-1	743 (800-1)	900-2¾	900-3
			883 (900-2¾)	883 (900-3)

ELEV 17	TDZE 4R 11
	TDZE 4L 10

HIRL all rwys  
REIL Rws 11, 22R and 29  
TDZL/RCLS all rwys

FAF to MAP 5.2 NM					
Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44

NE-2, 11 JUN 2026 to 09 JUL 2026

NE-2, 11 JUN 2026 to 09 JUL 2026