

ILS RWY 25 (CAT II)

LOC I-TYV 109.9	APCH CRS 252°	Rwy ldg 12,001 TDZE 301 Arprt Elev 312	[USAF]	LITTLE ROCK AFB (KLRF)
---------------------------	-------------------------	---	--------	------------------------


RNP APCH. RNAV1-GPS or RADAR required.		ALSF-2 	MISSED APPROACH: Climb to 900 then climbing right turn to 3000 direct HERCK and hold.
--	--	------------	---

ATIS ★ 119.175 251.1	APP CON 119.5 306.2	TOWER 120.6 269.075	GND CON 132.8 275.8
--------------------------------	-------------------------------	-------------------------------	-------------------------------



CATEGORY II ILS-SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED

ALTERNATE MISSED APPROACH: Climbing to 3000 fly runway heading until 2 DME, then turn right heading 360° expect further clearance from ATC.



PROCEDURE EFFECTIVE BY NOTAM



ATC RADAR required for holding above 4000' or greater than 200 KIAS.





CAT E Act: RADAR required when R-2403 active



EMERG SAFE ALT 100 NM 4000

ELEV 312	TDZE 301
----------	----------



CATEGORY	A	B	C	D	E
S-ILS 25	RA 94/12		100	DA 401	

HIRL Rwy 07-25
TDZL/RCLS Rwy 25

ILS RWY 25 (CAT II)

SC-1, 11 JUN 2026 to 09 JUL 2026

SC-1, 11 JUN 2026 to 09 JUL 2026