

| | | | |
|--|------------------------|-----------------------------|--------------------------------------|
| WAAS CH 61002 W28A | APP CRS 276° | Rwy Ldg TDZE Apt Elev | 8394 7 65 |
|--|------------------------|-----------------------------|--------------------------------------|

RNAV (GPS) Y RWY 28R

FORT LAUDERDALE/HOLLYWOOD INTL (FLL)


RNP APCH - GPS.

⚠ Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. Inop table does not apply to LPV all Cats. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 7°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to 1½ SM and LNAV Cats C/D to 1¼ SM.





MISSED APPROACH:
Climb to 800 then climbing right turn to 4000 direct HUKUK and hold, continue climb-in-hold to 4000.

| | | | |
|------------------------|---------------------------------------|---|-------------------------|
| D-ATIS 135.0 | MIAMI APP CON 133.775 285.6 | FORT LAUDERDALE TOWER 119.3 257.8 | GND CON 121.4 |
|------------------------|---------------------------------------|---|-------------------------|



| | | |
|---------|----------|--------|
| ELEV 65 | D | TDZE 7 |
|---------|----------|--------|



| CATEGORY | A | B | C | D |
|--------------|--------|-------------|---------------------|---------------------|
| LPV DA | | 257/40 | 250 (200-¾) | |
| LNAV/VNAV DA | | 581-1¼ | 574 (600-1¼) | |
| LNAV MDA | 620/24 | 613 (600-½) | 620-1¾ 613 (600-1¾) | |
| CIRCLING | 680-1 | 615 (700-1) | 800-2 735 (800-2) | 800-2¼ 735 (800-2¼) |

SE-3, 11 JUN 2026 to 09 JUL 2026

SE-3, 11 JUN 2026 to 09 JUL 2026