


LOC I-BER	APP CRS	Rwy Ldg
108.9	234°	6790
		TDZE
		18
		Apt Elev
		20

ILS Z or LOC Z RWY 23
ADAK (ADK) (PADK)

ADF and DME required.	MALS	MISSED APPROACH: Climb to 5400 direct ADK NDB/DME and on the 241° bearing from ADK NDB/DME to COMAT/ADK 10 DME and left turn direct ADK NDB/DME and hold. Missed approach requires minimum climb of 409 feet per NM to 2700; if unable to meet climb gradient, see ILS Y or LOC Y RWY 23.
⚠ Circling NA at night. Circling NA northwest of Rwy 5-23. Rwy 23 helicopter visibility reduction below ¾ SM NA. DME from ADK NDB. Simultaneous reception of I-BER and ADK DME required. Cat E for USAF/USN use only.	⚠	

AWOS-3P 134.5	ANCHORAGE CENTER 126.4 254.3	CTAF 122.9
------------------	---------------------------------	---------------



5400	ADK	ADK	COMAT	ADK	
↑		ADK 241°	ADK 10		
*LOC only					
ADK NDB/DME	ZUXUN	WIBAV	GUISE	GIDKE	
	ADK 2.8	ADK 4.9	ADK 9.7	ADK 14.7	
			2900	234°	
			2900	4500	
		760*		GS 3.50°	
				TCH 53	
	0.8	2.1 NM	4.7 NM	5.1 NM	
CATEGORY	A	B	C	D	E
S-ILS 23	309/50 291 (300-1)				
S-LOC 23	480/55 462 (500-1)		480-1 3/8 462 (500-1 3/8)		
CIRCLING	720-1 700 (700-1)		1060-3	2400-3	2440-3
			1040 (1100-3)	2380 (2400-3)	2420 (2500-3)

