

APP CRS	Rwy Ldg	11014
063°	TDZE	256
	Apt Elev	305

RNAV (RNP) Z RWY 6L

GUAM INTL (GUM)(PGUM)

RNP AR APCH - GPS.

▼

For uncompensated Baro-VNAV systems, procedure NA below 19°C or above 48°C. For inop ALS, increase RNP 0.30* visibility to ¾ SM and RNP 0.30 visibility to 1½ SM.

MALSR

AS

MISSED APPROACH: Climb to 3000 on 063° track to WABOX and hold.

*Missed approach requires minimum climb of 276 feet per NM to 1400.

ATIS	GUAM CERAP	AGANA TOWER	GND CON
119.0	119.8 269.0	118.1 340.2	121.9 336.4

WUVEN 15900
3000 (35.9)
1.66°

Procedure NA for arrivals at WUVEN on A597 northwest bound.

Procedure NA for arrivals at PULEE on G467 R596 west bound.

(IAF) PULEE 13300
3000 102° (32.6)

(IAF) RASPE 4500 210K
3000 5.3° (5)
2000 063° (7)

(IF) OBALE
3000 3.33° (11)

(FAF) ADEDE
3000 063° (5.3)

RW06L

063° (13.7)

MISSED APCH FIX
4 NM
063°
243°
WABOX

MSA RW06L 25 NM
2600

Procedure NA for arrivals at ASADE on B586 southeast bound.

(IAF) BURLE 6100
3000 3.37° (28.6)

ASADE 15100

OBALE VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73)

GP 3.00° TCH 55

3000

063°

2000

7 NM

5.3 NM

WABOX

3000

063° tr

CATEGORY	A	B	C	D
RNP 0.30 DA*		514-½	258 (300-½)	
RNP 0.30 DA		656-⅝	400 (400-⅝)	

AUTHORIZATION REQUIRED

ELEV 305 TDZE 256

GP 3.00° TCH 55

063°

0.5% UP

0.7% DOWN

12014 X 150

0.8% UP

0.6% DOWN

TWR

241°

HIRL all Rwys

TAMUNING, GU
Orig-F 02OCT25

13°29'N-144°48'E

GUAM INTL (GUM)(PGUM)

RNAV (RNP) Z RWY 6L

PAC, 14 MAY 2026 to 09 JUL 2026

PAC, 14 MAY 2026 to 09 JUL 2026