FORT BELVOIR, VIRGINIA

ILS or LOC RWY 32

LOC/DME I-DAA	APCH CRS	Rwy ldg	4529
108.9	322°	TDZE	68
Chan 26		Arpt Elev	74

[USA] DAVISON AAF (FORT BELVOIR) (KDAA)

RADAR required for procedure entry from DCA VOR.

▼ * When ALS inop, increase RVR to 45, vis to ⅞ mile.
** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile, CAT CD vis to 1⅜ miles.
*** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile, CAT CD vis to 1⅝ miles.

MALSF

MISSED APPROACH: Climb to 800, then climbing left turn to 3000 direct to HAXIL (DCA R-181/ 17.4 DME) and hold. Continue climb in hold to 3000.

ATIS	POTOMAC APP CON	TOWER ★	GND CON
128.175	118.95 319.1	124.275 (CTAF) Ⓒ 229.4	121.9 351.8

† If local altimeter setting not received, use Ronald Reagan Washington National altimeter setting.

Visibility reduction by helicopters not authorized.

WASHINGTON 111.0 DCA Chan 47

7400

Feeder from DCA for contingency use only.

LOCALIZER 108.9 I-DAA Chan 26

MSA 25 NM FROM AIRPORT 2600

EMERG SAFE ALT 100 NM 5300

VDP not authorized with KDCA altimeter.

HAXIL DCA 17.4 I-DAA 13 One Minute Holding Pattern

TACIT DCA R-194

EDCUT I-DAA 5.2

I-DAA 2.3

GS 3.00° TCH 34

4.4 NM

(IF/IAF) HAXIL DCA 17.4 I-DAA 13 3000

HOLD 3000

ELEV 74 TDZE 68

HIRL Rwy 14-32 Ⓒ

5421 x 75

TWR 117

0.5% DOWN

CATEGORY	A	B	C	D
S-ILS 32*	348/40 280 (300-¾)			
S-LOC 32**	580/40 512 (600-¾)		580-1¼ 512 (600-1¼)	
CIRCLING	680-1 606 (700-1)	720-1 646 (700-1)	760-2 686 (700-2)	1000-3 926 (1000-3)
† RONALD REAGAN WASHINGTON NATIONAL ALTIMETER SETTING MINIMUMS				
S-ILS 32	388/40 320 (400-¾)			
S-LOC 32***	620/40 552 (600-¾)		620-1⅜ 552 (600-1⅜)	
CIRCLING	720-1 646 (700-1)	760-1 686 (700-1)	800-2 726 (800-2)	1040-3 966 (1000-3)

FAF to MAP 4.4 NM					
Knots	60	90	120	150	180
Min:Sec	4:24	2:56	2:12	1:46	1:28

NE-3, 11 JUN 2026 to 09 JUL 2026
NE-3, 11 JUN 2026 to 09 JUL 2026