


WAAS CH 45520 W33A	APP CRS 326°	Rwy Ldg 4000 TDZE 984 Apt Elev 984
--	------------------------	---

RNAV (GPS) RWY 33



BRENNER FLD (FNB)

RNP APCH - GPS	MISSED APPROACH: Climb to 3000 direct COVUT and hold.
<p>▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. Baro-VNAV NA when using AFK altimeter setting. When local altimeter not received, use AFK altimeter setting and increase LPV DA to 1338 and LNAV/VNAV DA to 1380, increase all MDAs 120 feet.</p>	

ASOS 119.275	ST JOSEPH APP CON * 120.35 360.8	UNICOM 122.8 (CTAF) 0
------------------------	--	---------------------------------



ELEV 984	TDZE 984
MIRL Rwy 15-33	REIL Rwy 15 and 33



CATEGORY	A	B	C	D
LPV DA	1234-1	250 (300-1)		NA
LNAV/VNAV DA	1276-1	292 (300-1)		NA
LNAV MDA	1380-1	396 (400-1)		NA
CIRCLING	1560-1	576 (600-1)		NA

NC-2, 11 JUN 2026 to 09 JUL 2026

NC-2, 11 JUN 2026 to 09 JUL 2026