

WAAS CH 62800 W09D	APP CRS 095°	Rwy Ldg TDZE 1019 Apt Elev 1026
--	------------------------	---

RNAV (GPS) RWY 9L


HARTSFIELD/JACKSON ATLANTA INTL (ATL)

RNP APCH.


▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C or above 54°C. Rwy 9L helicopter visibility reduction below RVR 4000 NA. Simultaneous approach authorized with Rwy 8L or 8R or 10, or Rwy 8L and 10. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MISSED APPROACH: Climb to 4000 direct LEADR and on track 092° to CONNI and hold.

D-ATIS	ATLANTA APP CON	ATLANTA TOWER						ALL RWYS	GND CON	ALL RWYS
119.65	134.725 379.9	8L-26R	8R-26L	9L-27R	9R-27L	10-28			(8L-26R,8R-26L) (9L-27R,9R-27L)	10-28
		119.1	125.325	123.85	119.3	119.5	254.4	121.9	121.75	121.65 254.4



RYENN	AAKAY	ARRBE	HRDEY	VINII	LEADR	CONNI
7000	6000	5000	4000	2700	4000	
GP 3.00° TCH 56						
*LNAV only.						
*1.2 NM to RW09L						
RW09L						
3.5 NM 3.7 NM 3.5 NM 5 NM 3.9 NM 1.2 NM						
CATEGORY	A	B	C	D		
LPV DA	1359/50		340 (400-1)			
LNAV/VNAV DA	1405/60		386 (400-1¼)			
LNAV MDA	1480/55	461 (500-1)	1480-1⅜		461 (500-1⅜)	



SE-4, 09 JUL 2026 to 06 AUG 2026

SE-4, 09 JUL 2026 to 06 AUG 2026