




WAAS CH 90100 W36D	APP CRS 003°	Rwy Ldg 8390 TDZE 727 Apt Elev 748
--	------------------------	---

RNAV (GPS) Y RWY 36R

CHARLOTTE/DOUGLAS INTL (CLT)

RNP APCH.			ALSF-2		MISSED APPROACH:
⚠ Circling NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C or above 54°C. Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. For inop ALSF, increase LNAV/VNAV all Cats visibility to 1½ mile.			ⓘ		Climb to 1320 then climbing right turn to 4000 direct LOCAS and hold.
D-ATIS	CHARLOTTE APP CON		CHARLOTTE TOWER		GND CON
121.15	128.325 (001°-119°)	257.2 (180°-359°)	118.1 257.8 (18L-36R)		121.8 348.6 (W)
	120.05 (120°-295°)	307.8 (360°-179°)	126.4 257.8 (1R-19L)		121.9 348.6 (E)
	134.75 (296°-360°)		133.35 257.8 (1L-19R)		



1320	4000	LOCAS	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 74).				HEKAM	
							JENDA	
*LNAV only.							GP 3.00° TCH 55'	
CATEGORY		A		B		C	D	
LPV	DA	927/18		200 (200-½)				
LNAV/ VNAV	DA	1229-1¼		502 (500-1¼)				
LNAV MDA		1320/24	593 (600-½)	1320-1¼		593 (600-1¼)		
CIRCLING		1380-1	632 (700-1)	1500-2¼ 752 (800-2¼)		1500-2½ 752 (800-2½)		