



LOC/DME I-ONB 109.1 Chan 28	APP CRS 281°	Rwy Ldg 8000 TDZE 813 Apt Elev 815
---	------------------------	---

ILS or LOC RWY 28R
JOHN GLENN COLUMBUS INTL (CMH)

DME or RADAR required.	MALSR	MISSED APPROACH: Climb to 1400 then climbing right turn to 3000 direct APE VORTAC and hold.
Simultaneous approach authorized. Autopilot coupled approach NA. For inop ALS, increase S-LOC 28R Cat C/D visibility to 1½ SM.		

D-ATIS 124.6	COLUMBUS APP CON 125.95 371.975	COLUMBUS TOWER 132.7 257.8	GND CON 121.9 348.6
------------------------	---	--------------------------------------	-------------------------------



1400	3000	APE	WEEKZ I-ONB 6	WINAT I-ONB 9.2
UNOIT I-ONB 3.5	I-ONB 2.8	2300	3300	GS 3.00° TCH 50
1.3 NM	0.7 NM	2.5 NM	3.2 NM	
CATEGORY	A	B	C	D
S-ILS 28R	1013/24 200 (200-½)			
S-LOC 28R	1280/24	467 (500-½)	1280/50	467 (500-1)
CIRCLING	1340-1	525 (600-1)	1520-2 705 (800-2)	1520-2¼ 705 (800-2¼)

EC-2, 09 JUL 2026 to 06 AUG 2026

EC-2, 09 JUL 2026 to 06 AUG 2026