

WAAS CH 53300 W27B	APP CRS 276°	Rwy Ldg TDZE 630 Apt Elev 645
--	------------------------	---

RNAV (GPS) RWY 27L

DETROIT METRO WAYNE COUNTY (DTW)

RNP APCH

▼


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 5000. ** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH:

Climb to 1100 then climbing left turn to 4000 direct JUSUL and hold.

D-ATIS 133.675	DETROIT APP CON 124.05 284.0	METRO TOWER 128.75 317.725	GND CON 121.8 (NW) 119.45 (NE) 132.725 (SW) 119.25 (SE)
--------------------------	--	--------------------------------------	---



1100

4000

JUSUL

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).

*LNAV only.

	1.2	2.9 NM	3.1 NM	3.1 NM	3.1 NM	3.1 NM	3.1 NM	
CATEGORY	A	B	C	D				
LPV DA**	830/24		200 (200-½)					
LNAV/VNAV DA	958/30		328 (400-⅝)					
LNAV MDA	1080/24	450 (500-½)	1080/45	450 (500-⅞)				
CIRCLING	1180-1	535 (600-1)	1180-1½ 535 (600-1½)	1240-2 595 (600-2)				

