

WAAS
CH **42612**
W16A

APP CRS
164°

Rwy Ldg **7502**
TDZE **710**
Apt Elev **710**

RNAV (GPS) RWY 16
FORT WORTH MEACHAM INTL (FTW)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA.

⚠

** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 3000 direct PAXXE and hold.

ATIS 120.7	LONE STAR APP CON 118.1 306.95 (N) 135.975 379.9 (S)	MEACHAM TOWER 118.3 257.8	GND CON 121.9
----------------------	--	-------------------------------------	-------------------------

Procedure NA for arrivals on UKW VORTAC via V17-161 northbound.

Procedure details:
- BOWIE UKW (35.8) 3000 ft
- (IF/IAF) WOROD (164°)
- (FAF) MESDE (164°)
- 2500 ft MDA
- 990 ft AGL
- 974 ft AGL
- RW16
- MISSED APCH FIX PAXXE (164°)
- 4 NM holding pattern at WOROD (344°)
- 3000 ft MDA
- GP 3.00° TCH 57
- 6 NM, 3.9 NM, 1.5 NM segments
- 1.5 NM to RW16 (LNAV only)

ELEV 710

D

TDZE 710

Procedure details:
- 164° heading
- 2500 ft MDA
- 3000 ft NoPT (5)
- GP 3.00° TCH 57
- 6 NM, 3.9 NM, 1.5 NM segments
- 1.5 NM to RW16 (LNAV only)

4 NM Holding Pattern	WOROD	MESDE	3000	PAXXE
3000	344°	164°	164°	164°
GP 3.00° TCH 57	2500	1.5 NM to RW16	*LNAV only.	
6 NM	3.9 NM	1.5 NM		
CATEGORY	A	B	C	D
LPV DA **	910/24	200 (200-½)		
LNAV/VNAV DA	1284-1½	574 (600-1½)		
LNAV MDA	1240/24	530 (600-½)	1240/50 530 (600-1)	1240/60 530 (600-1¼)
CIRCLING	1260-1 550 (600-1)	1280-1 570 (600-1)	1340-1¾ 630 (700-1¾)	1500-2½ 790 (800-2½)

FORT WORTH, TEXAS

Amdt 1C 19MAY22

32°49'N-97°22'W

FORT WORTH MEACHAM INTL (FTW)

RNAV (GPS) RWY 16