

WAAS CH 72902 W27A	APP CRS 269°	Rwy Ldg TDZE Apt Elev	8175 862 869
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 27

THE EASTERN IOWA (CID)


▼ Baro-VNAV NA when using Iowa City altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA.

▲ When local altimeter setting not received, use Iowa City altimeter setting; increase LPV DA to 1192 feet; increase LNAV/VNAV DA to 1243 feet; increase all MDAs 80 feet and Circling visibility Cat C and D ¼ SM. For inop MALS increase LNAV/VNAV Cat D visibility to RVR 5000 and LNAV Cat D visibility to RVR 6000. VDP NA when using Iowa City altimeter setting.

MALS

MISSED APPROACH:
Climb to 2500 direct
CUKLA and hold.

ATIS 124.15	CEDAR RAPIDS APP CON★ 119.7 266.8	CEDAR RAPIDS TOWER★ 118.7 (CTAF) 266.8	GND CON 121.6	UNICOM 122.95
-----------------------	---	--	-------------------------	-------------------------



ELEV 869 D TDZE 862

MIRL Rwy 13-31
HIRL Rwy 9-27
REIL Rwy 13

2500	CUKLA	WAVUM	JUTUS	4 NM Holding Pattern
*LNAV only	*1.1 NM to RWY27	269°	2700	089° 2700
	-1.1	4.4 NM	6 NM	GP 3.00° TCH 49
CATEGORY	A	B	C	D
LPV DA	1112/24 250 (300-½)			
LNAV/VNAV DA	1163/24 301 (300-½)			1163/40 301 (300-¾)
LNAV MDA	1260/24 398 (400-½)			1260/50 398 (400-1)
CIRCLING	1280-1 411 (500-1)	1320-1 451 (500-1)	1560-2 691 (700-2)	1560-2¼ 691 (700-2¼)