

WAAS
CH **69310**
W10A

APP CRS
105°

Rwy Ldg
TDZE **2869**
Apt Elev **2872**

RNAV (GPS) RWY 10

MIDLAND INTL AIR AND SPACE PORT (M.A.F.)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C (13°F) or above 25°C (77°F). Circling Rwy 16L NA at night. DME/DME RNP-0.3 NA.
** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH:
Climb to 4700 direct
EASYY and hold.

ATIS
126.8 235.975

MIDLAND APP CON*
124.6 290.4

MIDLAND TOWER*
118.7 (CTAF) 0273.45

GND CON
121.9 348.6

UNICOM
122.95

ELEV 2872

D

TDZE 2869

5 NM
Holding Pattern

JEMMO

BOOST

4700

EASYY

*LNAV only

5000

284°

104°

104°

4900

105°

1.8 NM to RWY10

GP 3.00°
TCH 54

7.3 NM

4.4 NM

1.8

CATEGORY	A	B	C	D
LPV DA **	3069/24 200 (200-½)			
LNAV/VNAV DA	3394-1¼ 525 (600-1¼)			
LNAV MDA	3480/24	611 (700-½)	3480-1⅓	611 (700-1⅓)
CIRCLING	3480-1	608 (700-1)	3480-1¾	3520-2
			608 (700-1¾)	648 (700-2)

REIL Rwy 34L

MIRL Rwy 4-22 and 16L-34R

HIRL Rwy 10-28 and 16R-34L

MIDLAND, TEXAS

MIDLAND INTL AIR AND SPACE PORT (M.A.F.)

Amcl 2C 12OCT17

31°57'N-102°12'W

RNAV (GPS) RWY 10