

RNAV (GPS) RWY 15
MOBILE RGNL (MOB)

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C or above 42°C. For inop ALS, increase LNAV Cats C/D visibility to RVR 6000.
ASR *RVR 1800 authorized with use of FD or AP or HUD to DA.

MISSED APPROACH: Climb to 2000 direct JOTEN and on track 189° to SAINT and hold.

Diagram illustrating a flight profile with various waypoints and altitudes:

- Initial Climb:** 30 NM to BAYAS (NoPT) at 2800, 22 NM to BAYAS at 2000, 237° heading.
- Hold:** 4 NM, HOLD 6000/2000, 147° heading.
- Descent:** 327° heading, (IF/IAF) BAYAS.
- Climb:** 1800, 147° heading, (6.7).
- Descent:** 498, (FAF) CAYAT.
- Climb:** 365, DICAD, 2.4 NM to RW15.
- Descent:** 189°, 189° heading, (5.7), JOTEN.

Missed Approach Procedures:

- BAYAS:** 30 NM to BAYAS (NoPT) at 2800, 22 NM to BAYAS at 2000, 237° heading.
- JOTEN:** 189° heading, 189° heading, (5.7).

ELEV	TDZE
219	215

SE-4, 09 JUL 2026 to 06 AUG 2026

SE-4, 09 JUL 2026 to 06 AUG 2026