

APP CRS	Rwy Ldg	8995
227°	TDZE	26
	Apt Elev	27

RNAV (RNP) Y RWY 23

NORFOLK INTL (ORF)

For uncompensated Baro-VNAV systems, procedure NA below -9°C (16°F) or above 54°C (130°F). GPS required. For inop ALS, increase RNP 0.10 DA visibility all Cats to 1½ SM, increase RNP 0.30 DA visibility all Cats to 1¾ SM.

MALSR

MISSED APPROACH: Climb to 2000 on track 227° to CALEY and hold.

ATIS 127.15	NORFOLK APP CON 118.9 353.7	NORFOLK TOWER 120.8 257.8	GND CON 121.9
----------------	--------------------------------	------------------------------	------------------

RADAR REQUIRED

MISSED APCH FIX

CALEY

045°

225°

4 NM

CATEGORY	A	B	C	D
RNP 0.10 DA		432-¾	406 (500-¾)	
RNP 0.30 DA		491-1	465 (500-1)	

ELEV 27

TDZE 26

HIRL Rwy 5-23

2000	tr 227°	CALEY	See planview for multiple IF locations.	BAAGN
				1200
				1200
				GP 3.00°
				TCH 55
				3.6 NM
CATEGORY	A	B	C	D
RNP 0.10 DA		432-¾	406 (500-¾)	
RNP 0.30 DA		491-1	465 (500-1)	
AUTHORIZATION REQUIRED				

NORFOLK, VIRGINIA

Amdt 1 01FEB18

36°54'N-76°12'W

NORFOLK INTL (ORF)

RNAV (RNP) Y RWY 23