

OLGUY THREE DEPARTURE (RNAV)

TOP ALTITUDE:
Assigned by ATC

TAKEOFF MINIMUMS:

R_{wys} 13, 17L/R, 18, 31, 35L/R, 36:

Standard with minimum climb of 500' per NM to 1800.

NOTE: RADAR required.

NOTE: DME/DME/IRU or GPS required.

NOTE: RNAV 1.

D-ATIS

125.85

CLINC DEL
19495

24.35 CNID CON

3486

ROGERS TOWER

119.35 269.45

ROCKE CITY DEP

24.6 266.8



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 13: Climb heading 131° to 1800, then right turn heading

201° or as assigned by ATC, expect RADAR vectors to BEEDI thence

TAKEOFF RWYS 17L/R, 18: Climb heading 176° to 1800, then right turn heading

201° or as assigned by ATC, expect RADAR vectors to BEEDL, thence

TAKEOFF RWY 31: Climb heading 311° to 1800, then heading 311° or as assigned

by ATC, expect RADAR vectors to BEEDI, thence

TAKEOFF RWYS 35L/R, 36: Climb heading 356° to 1800, then left turn heading

311° or as assigned by ATC, expect RADAR vectors to BEEDL, thence

... on track 267° to OLGUY, then on (transition). Maintain 5000 or as assigned

by ATC. Expect filed altitude 10 minutes after departure.

GRUVN TRANSITION (OLGUY3.GRUVN):

YOUSE TRANSITION (OLGUY3.YOUSE):

NOTE: Chart not to scale.