

APP CRS
356°

Rwy Ldg
TDZE
Apt Elev

9802
1294
1296

RNAV (RNP) Z RWY 35R

OKC WILL ROGERS INTL (OKC)

ASR

For uncompensated Baro-VNAV systems, procedure NA below -12°C (11°F) or above 54°C (130°F). GPS required. Simultaneous approach authorized with Rwy 35L.
Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ALSf-2

MISSED APPROACH: Climb to 5000 on track 356° to ATREC and hold, continue climb-in-hold to 5000.

D-ATIS 125.85	OKE CITY APP CON 124.6 266.8	ROGERS TOWER 119.35 269.45	GND CON 121.9 348.6
------------------	---------------------------------	-------------------------------	------------------------

ELEV 1296 **D** TDZE 1294

REIL Rws 13 and 31
TDZL/RCLS Rwy 35R
MIRL Rwy 13-31
HIRL Rws 17L-35R and 17R-35L

5000

tr 356°

ATREC

See planview for multiple IF locations.

RW35R

356°

CARLY 2300

2300

GP 3.00°

TCH 56

CATEGORY	A	B	C	D
RNP 0.16 DA		1570/24	276 (300-½)	
RNP 0.30 DA		1674/39	380 (400-¾)	

AUTHORIZATION REQUIRED

OKLAHOMA CITY, OKLAHOMA

Amtd 2C 07DEC17

35°24'N-97°36'W

OKC WILL ROGERS INTL (OKC)

RNAV (RNP) Z RWY 35R