

WAAS CH 70729 W07A	APP CRS 073°	Rwy Ldg TDZE 109 Apt Elev 113
--	------------------------	---

RNAV (GPS) RWY 7

ORLANDO EXEC (ORL)

RNP APCH-GPS.

⚠

Circling Rwy 31 NA at night. Rwy 7 helicopter visibility reduction below ¾ SM NA.

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 2°C or above 54°C.


⚠

For inop ALS, increase LPV all Cats visibility to RVR 4500, increase LNAV/VNAV all Cats visibility to RVR 5000, increase LNAV Cat A/B visibility to RVR 5500 and Cats C/D to 1¾ SM. In minimum visibility conditions, bright lights on highway ½ mile south of airport may be mistaken for runway lights.

MALSR

MISSED APPROACH:
Climb to 1500 direct MSHEL, cross MSHEL at 1500, then climb to 1600 on track 039° to OVIDO and hold.

ATIS 127.25	ORLANDO APP CON 119.4 351.9 (7) 125.225 351.9 (25)	EXECUTIVE TOWER ★ 118.7 (CTAF) 0 239.0	GND CON 121.4 239.0	UNICOM 122.95
-----------------------	--	---	-------------------------------	-------------------------



4 NM Holding Pattern		ESRAQ	DNMR	1500	MSHEL 1500	1600	OVIDO
6000 ← 253°		073° →	2000	SWLTR 2.8 NM to RWY 07	1.9 NM to RWY 07	RWY 07	
GP 3.00°		2000	1020				
TCH 52		6.2 NM	3 NM	0.9	1.9		
CATEGORY	A	B	C	D			
LPV DA		391/40	282 (300-¾)				
LNAV/VNAV DA		447/40	338 (400-¾)				
LNAV MDA	740/40	631 (700-¾)	740-1⅜	631 (700-1⅜)			
CIRCLING	740-1	627 (700-1)	860-2¼	860-2½			
			747 (800-2¼)	747 (800-2½)			