


WAAS CH 73011 W07B	APP CRS 078°	Rwy Ldg TDZE 1116 Apt Elev 1135
--	------------------------	---


RNAV (GPS) Y RWY 7R

PHOENIX SKY HARBOR INTL (PHX)

RNP APCH - GPS.		MALSR	MISSED APPROACH: Climb to 5000 direct NAVOQ and via 110° track to IWA VORTAC and hold.
▼ For inop ALS, increase visibility LPV all Cats to ¾ SM, LNAV/VNAV all Cats to 1½ SM, LNAV Cats A/B to 1 SM and C/D to 1¾ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 46°C. Rwy 7R helicopter visibility reduction below ¾ SM NA. Simultaneous approach authorized. Use of FD or AP providing RNAV track guidance required during simultaneous operations. LNAV procedure NA during simultaneous operations.			
D-ATIS 127.575	PHOENIX APP CON 128.65 353.9	PHOENIX TOWER 118.7 278.8 (8-26) 120.9 254.3 (7L-25R, 7R-25L)	GND CON 119.75 269.2 (N) 132.55 269.2 (S)



ELEV 1135	D	TDZE 1116
-----------	----------	-----------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 70).			
5 NM Holding Pattern	JEPES	OVNUY	ADWOT 2.1 NM to RW07R
4300	258°	078°	1840
GP 3.00° TCH 57	6 NM	3.6 NM	0.9 1.2 NM
CATEGORY	A	B	C
LPV DA	1390-¾	274 (300-¾)	
LNAV/VNAV DA	1520-1	404 (400-1)	
LNAV MDA	1580-¾	464 (500-¾)	1580-1 464 (500-1)
CIRCLING	1740-1	605 (700-1)	2040-2¾ 905 (1000-2¾) 2560-3 1425 (1500-3)

SW-4, 09 JUL 2026 to 06 AUG 2026

SW-4, 09 JUL 2026 to 06 AUG 2026