



WAAS CH 86611 W08A	APP CRS 078°	Rwy Ldg 10591 TDZE 1118 Apt Elev 1135
--	------------------------	--

RNAV (GPS) Y RWY 8

PHOENIX SKY HARBOR INTL (PHX)

RNP APCH - GPS.		MALSF 	MISSED APPROACH: Climb to 3000 then climbing left turn to 5000 direct AVENT and hold.
Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Inop table does not apply to LPV all Cats. For inop ALS, increase LNAV Cats C and D visibility to 2 SM.			
D-ATIS 127.575	PHOENIX APP CON 128.65 353.9	PHOENIX TOWER 118.7 278.8 (8-26) 120.9 254.3 (7L-25R, 7R-25L)	GND CON 119.75 269.2 (N) 132.55 269.2 (S)



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 69).			
5 NM Holding Pattern			
GP 3.00° TCH 54			
CATEGORY A B C D			
LPV DA 1368-3/4 250 (300-3/4)			
LNAV MDA 1860-3/4 742 (800-3/4) 1860-1 742 (800-1) 1860-1 7/8 742 (800-1 7/8)			
CIRCLING 1860-1 725 (800-1) 1860-1 7/4 725 (800-1 1/4) 2040-2 3/4 905 (1000-2 3/4) 2340-3 1205 (1300-3)			

SW-4, 09 JUL 2026 to 06 AUG 2026

SW-4, 09 JUL 2026 to 06 AUG 2026