

|                                        |                        |                                                                  |
|----------------------------------------|------------------------|------------------------------------------------------------------|
| WAAS<br>CH <b>87021</b><br><b>W24A</b> | APP CRS<br><b>244°</b> | Rwy Ldg TDZE<br><b>7603</b><br><b>534</b><br>Apt Elev <b>617</b> |
|----------------------------------------|------------------------|------------------------------------------------------------------|

RNAV (GPS) RWY 24

ST LOUIS LAMBERT INTL (STL)

|                                                                                                                                                                                                                                          |                                           |                                        |                                                                                                                   |                                                                                  |       |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|----------------------------------------|-------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|-------|
| RNP APCH - GPS.<br>▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Inop table does not apply to LPV. For inop ALS, increase LNAV/VNAV Cat E visibility to 1 3⁄8 SM and LNAV Cat E visibility to 1 3⁄8 SM. |                                           |                                        | MALS<br>                         | MISSED APPROACH: Climb to 3000 direct SORUE and on track 294° to AUGST and hold. |       |
| D-ATIS<br><b>125.025</b><br><b>379.925</b>                                                                                                                                                                                               | ST. LOUIS APP CON<br><b>132.125 360.6</b> | ST. LOUIS TOWER<br><b>120.05 284.6</b> | GND CON<br><b>121.9 348.6</b> (Inbound)<br><b>121.65 377.175</b> (Outbound)<br><b>118.925 227.125</b> (Rwy 11/29) | CLNC DEL<br><b>119.5 363.1</b>                                                   | CPDLC |

