

WAAS CH 90229 W36A	APP CRS 355°	Rwy Ldg 12250 TDZE 496 Apt Elev 542
--	------------------------	--

RNAV (GPS) Y RWY 36L

AUSTIN-BERGSTROM INTL (AUS)



RNP APCH-GPS.

Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C. Inop table does not apply to LPV all Cats. For inop ALS, increase LNAV/VNAV Cat E visibility to 1½ SM, LNAV Cat E visibility to 1¼ SM.

MALS
④

MISSED APPROACH: Climb to 1700 then climbing left turn to 3500 direct GARDS and hold.

D-ATIS 124.4	AUSTIN APP CON 127.225 317.65 (E) 120.875 270.25 (S) 119.0 370.85 (W)	AUSTIN TOWER 121.0 281.5	GND CON 121.9 348.6
------------------------	---	------------------------------------	-------------------------------



1700	3500	GARDS	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 60).		LAMAS
↑	↙	△	FUNNN	BIIRD	CAMDY
1.2 NM	0.6	1.5 NM	3 NM	6.3 NM	4 NM
WINKS 1.8 NM to RW36L	1.2 NM to RW36L	1600	1100	1600	2500
355°	355°	4000	5000	GP 3.00°	TCH 54
CATEGORY	A	B	C	D	E
LPV DA	696/40		200 (200-¾)		
LNAV/VNAV DA	970/60		474 (500-1¼)		
LNAV MDA	920/40	424 (400-¾)	920/50	424 (400-1)	
CIRCLING	1040-1 498 (500-1)	1120-1 578 (600-1)	1200-1¾ 658 (700-1¾)	1200-2 658 (700-2)	NA

SC-3, 09 JUL 2026 to 06 AUG 2026

SC-3, 09 JUL 2026 to 06 AUG 2026