

LAURENCE G HANSCOM FLD (BED)



DEPARTURE ROUTE DESCRIPTION

TAKEOFF ALL RUNWAYS: Climb on heading as assigned by ATC, thence....

....expect RADAR vectors to assigned route/navaid/fix. Maintain 2000. Expect clearance to filed altitude/flight level within ten (10) minutes after departure.

- NOTE: Non-RNAV equipped aircraft can expect vectors on assigned route.
- NOTE: BLZZR DEPARTURES expect vectors on BOS R-273, DME required.
- NOTE: BRUWN DEPARTURES expect vectors on BOS R-159, DME required.
- NOTE: CELTK DEPARTURES expect vectors on BOS R-114.
- NOTE: HYLND DEPARTURES expect vectors on BOS R-350, DME required.
- NOTE: PATSS DEPARTURES expect vectors on BOS R-260, DME required.
- NOTE: REVSS DEPARTURES expect vectors on BOS R-285, DME required.
- NOTE: SSOXS DEPARTURES expect vectors on BOS R-177.

TAKEOFF MINIMUMS:

- Rwys 5, 29: Standard.
- Rwy 11: 300-1 or Standard with minimum climb of 258' per NM to 400.
- Rwy 23: 300-1½ or Standard with minimum climb of 439' per NM to 400.