

NORWOOD FIVE DEPARTURE

BOSTON DEP CON
124.1 343.6
ATIS 119.95
CLNC DEL
121.8
GND CON
121.8
NORWOOD TOWER ★
126.0 (CTAF)

KENNEBUNK
117.1 ENE ---
Chan 118



PEASE

MANCH △

CAMBRIDGE
115.0 CAM ---
Chan 97




SYRACUSE
117.0 SYR ---
Chan 117



CHESTER
115.1 CTR ---
Chan 98



BARNES
113.0 BAF ---
Chan 77




TAKEOFF MINIMUMS:

- Rwy 10: 400-2½ or standard with minimum climb of 440'/NM to 300.
- Rwy 17: Standard.
- Rwy 28: Standard with minimum climb of 385'/NM to 400.
- Rwy 35: Standard with minimum climb of 260'/NM to 1800.

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)





DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 10: Climb on heading 104° to 1100, then as assigned by ATC, thence

TAKEOFF RUNWAY 17: Climb on assigned heading, thence...

TAKEOFF RUNWAY 28: Climb on heading 284° to 700, then as assigned by ATC, thence

TAKEOFF RUNWAY 35: Climb on heading 280° CW 330° as assigned by ATC, thence

. . . . for RADAR vectors to assigned route/NAVAID/fix. Maintain 2000. Expect clearance to filed altitude/flight level within ten (10) minutes after departure.

- NOTE: BLZZR DEPARTURES expect vectors on BOS R-273.
- NOTE: BRUWN DEPARTURES expect vectors on BOS R-159.
- NOTE: CELTK DEPARTURES expect vectors on BOS R-114.
- NOTE: HYLND DEPARTURES expect vectors on BOS R-350.
- NOTE: PATSS DEPARTURES expect vectors on BOS R-260.
- NOTE: REVSS DEPARTURES expect vectors on BOS R-285.
- NOTE: SSOXS DEPARTURES expect vectors on BOS R-177.

NE-1, 09 JUL 2026 to 06 AUG 2026

NE-1, 09 JUL 2026 to 06 AUG 2026