

WAAS CH 49119 W19B	APP CRS 196°	Rwy Ldg TDZE Apt Elev	7302 1320 1333
--	------------------------	-----------------------------	---

RNAV (GPS) Y RWY 19L


WICHITA DWIGHT D EISENHOWER NTL (ICT)

RNP APCH.


▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Simultaneous approach authorized with ILS or LOC RWY 19R. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSRMISSED APPROACH: Climb to 3600 direct YELOO and hold.

ATIS 125.15	WICHITA APP CON 126.7 353.5	WICHITA TOWER 118.2 257.8	GND CON 121.9 348.6
-----------------------	---------------------------------------	-------------------------------------	-------------------------------



ELEV 1333	D	TDZE 1320
-----------	----------	-----------



3600	YELOO	HELUM 1.7 NM to RWY 19L	KECHI	JAXSU	4 NM Holding Pattern
*LNAV only.		*1.1 NM to RWY 19L			
		1900*			GP 3.00° TCH 54
	1.1 NM	0.6	3.4 NM	8.1 NM	
CATEGORY	A	B	C	D	
LPV DA	1520-1/2		200 (200-1/2)		
LNAV/VNAV DA	1747-3/4		427 (500-3/4)		
LNAV MDA	1780-1/2		460 (500-1/2)		
			1780-7/8 460 (500-7/8)		
CIRCLING	1800-1		467 (500-1)		
			1980-1 647 (700-1 3/4)		
			1980-2 647 (700-2)		