

YIGO, GUAM I, GUAM

RNAV (GPS) RWY 24L

APCH CRS 244°	Rwy Idg 11,199 TDZE 607 Arpt Elev 617
-------------------------	--

(USAF)

ANDERSEN AFB (PGUA)

RNP APCH. DME/DME RNP - 0.3 NA

T * When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE RVR to 50, vis to 1 mile.
** Circling not authorized NW of Rwy 06L-24R.

(A₂)

MISSED APPROACH: Climb to 1 200, then climbing left turn to 3000 direct FOKAL and hold.

ATIS
118.175 254.325

GUAM APP CON/DEP CON
119.8 269.0

TOWER
126.2 233.7

GND CON
121.7 275.8

CAUTION: Environmentally Sensitive Area Flights along Andersen cliffline restricted to 1000' AGL or above.

All touchdown zones have a 1.0% down slope.

(IAF)
EDIAZ
3000

(IF/IAF)
LUAAP
2700

(FAF)
OWEND

RW24L

EMERG SAFE ALT 100 NM 2900

1200	3000	FOKAI
		

ELEV 617

TDZE 607

Figure 1 is a schematic diagram of a two-way road with two lanes. The top lane is labeled "10,527 x 200" and "0.7% UP". The bottom lane is labeled "11,199 x 200" and "0.5% DOWN". The diagram shows traffic flow with arrows and vehicle icons. A legend indicates "TWR BCN Z35".

CATEGORY	A	B	C	D	E
LNAV MDA*	940/40 333 (400-¾)		940/45 333 (400-⅞)		
CIRCLING**	1060-1 443 (500-1)	1080-1 463 (500-1)	1240-1¼ 623 (700-1¼)	1240-2 623 (700-2)	1240-2¼ 623 (700-2¼)

HIRL all rwys

YIGO, GUAM I, GUAM

13°35'N - 144°56'E

ANDERSEN AFB (PGUA)

Amdt 1 17JUN21
TERPS

RNAV (GPS) RWY 24L

PAC, 09 JUL 2026 to 03 SEP 2026