

LOC/DME I-CRP

110.3

Chan **40**

APP CRS

132°

Rwy Ldg

7510

TDZE

46

Apt Elev

46

ILS or LOC RWY 13

CORPUS CHRISTI INTL (CRP)

Autopilot coupled approach NA below 260.

For inop ALS, increase S-ILS 13 Cat E visibility to RVR 4000 and S-LOC 13 Cats C, D, and E visibility to RVR 5500.

*RVR 1800 authorized with use of FD or AP or HUD to DA.

MALS

MISSED APPROACH: Climb to 500 then climbing right turn to 2000 on heading 132° and CRP VORTAC R-169 to SOLON INT/CRP VORTAC 28 DME and hold.

ATIS 126.8	CORPUS APP CON 120.9 348.725	CORPUS TOWER 119.4 257.8	GND CON 121.9 269.15
----------------------	--	------------------------------------	--------------------------------

ELEV 46		D	TDZE 46			
132° 7510 X 150 TWR 31 36 6080 X 150 81 AS AS AS AS						
HIRL Rwy 13-31 and 18-36						
FAF to MAP 4.7 NM						
Knots	60	90	120	150		
Min:Sec	4:42	3:08	2:21	1:53		
CORPUS CHRISTI, TEXAS						
Amdt 28B 02NOV23						

Remain within 15 NM		CEVUS INT I-CRP 6.6 RADAR	500	2000	SOLON
			↑	hdg 132°	△
				CRP R-169	
		DOMIW INT I-CRP 3.6	I-CRP 2.5	HALVU I-CRP 1.9	
		720			
		3 NM	1.1	0.6	0.3
CATEGORY	A	B	C	D	E
S-ILS 13*	246/24 200 (200-½)				
S-LOC 13	400/24	354 (400-½)	400/30 354 (400-¾)		
CIRCLING	500-1 454 (500-1)	780-1 734 (800-1)	820-2¼ 774 (800-2¼)	820-2½ 774 (800-2½)	820-2¾ 774 (800-2¾)

CORPUS CHRISTI, TEXAS

Amdt 28B 02NOV23

27°46'N-97°30'W

CORPUS CHRISTI INTL (CRP)

ILS or LOC RWY 13