



RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -10°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500. When local altimeter setting not received, use Greenville downtown altimeter setting: increase LPV DA to 1193 feet; increase LNAV/VNAV DA to 1267 feet; increase all MDA 40 feet and LNAV Cat C/D visibility to RVR 4000; increase Circling Cat D visibility to 2½ SM. For inop ALS, when using Greenville downtown altimeter setting, increase LNAV/VNAV all Cats visibility to RVR 4500. VDP and Baro-VNAV NA when using Greenville downtown altimeter setting.

MALSR

MISSED APPROACH:
Climb to 3000 direct
OXABY and hold.

ATIS 134.25	GREER APP CON ★ 118.8 270.275	GREER TOWER ★ 120.1(CTAF) 0 251.15	GND CON 121.9	UNICOM 122.95
----------------	----------------------------------	---------------------------------------	------------------	------------------



CATEGORY	A	B	C	D
LPV DA	1164/24	200 (200-½)		
LNAV/VNAV DA	1238/24	274 (300-½)		
LNAV MDA	1360/24 396 (400-½)	1360/35 396 (400-¾)		
CIRCLING	1440-1 476 (500-1)	1480-1½ 516 (600-1½)	1700-2¼ 736 (800-2¼)	

