

WAAS CH 50440 W33A	APP CRS 325°	Rwy Ldg 5001 TDZE 41 Apt Elev 47
--	------------------------	---

RNAV (GPS) RWY 33R

WRIGHT AAF (FORT STEWART)/MIDCOAST RGNL (LHW)

RNP APCH.

⚠

Circling to Rwy 6R, 24L, 15R, 33L, 6L, 24R NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C or above 54°C. When local altimeter setting not received, use Savannah/Hilton Head Intl altimeter setting: increase LPV DA to 346 feet, LNAV/VNAV DA to 379 feet and all visibilities ½ mile; increase all MDAs 60 feet and LNAV and Circling Cats C and D visibility ¼ mile. Baro-VNAV NA when using Savannah Hilton Head Intl altimeter. Circling NA northeast of Rwy 15L-33R. Procedure NA when R-3005C/D or R-3007C is active and LHW Tower is closed.

MISSED APPROACH: Climb to 500 then climbing right turn to 4000 direct HARPS and hold.

ATIS 118.475	SAVANNAH APP CON* 120.4 353.775	WRIGHT TOWER * 126.25 (CTAF) 0 269.275	GND CON 121.7 273.575
------------------------	---	--	---------------------------------

ELEV 47	TDZE 41	500	4000	HARPS	VGSi and descent angles not coincident (VGSi Angle 3.00/TCH 65).			
		*LNAV only.		RICBO	2000	GP 3.00° TCH 51		
		RYW33R	TYNES 1.5 NM to RW33R	BAARD 1600	325°	1600		
		-1.5 NM		3.3 NM	6 NM			
		CATEGORY	A	B	C	D		
		LPV DA	291-1		250 (300-1)			
		LNAV/VNAV DA	324-1		283 (300-1)			
		LNAV MDA	420-1		379 (400-1)			
		CIRCLING	560-1 513 (600-1)	620-1 573 (600-1)	680-1¾ 633 (700-1¾)	680-2 633 (700-2)		

FORT STEWART (HINESVILLE), GEORGIA
Amdt 1B 11AUG22

WRIGHT AAF (FORT STEWART)/MIDCOAST RGNL (LHW)
31°53'N-81°34'W

RNAV (GPS) RWY 33R