

WAAS CH 86713 W26B	APP CRS 267°	Rwy Ldg 10001 TDZE 790 Apt Elev 794
--	------------------------	--

RNAV (GPS) RWY 26L

GERALD R FORD INTL (G.R.R)

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inoperative ALS, increase LNAV/VNAV Cat D visibility to RVR 5000.
** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH:

Climb to 2700 direct FERLI and track 267° to JAKES and hold.

ATIS 118.725	GREAT LAKES APP CON★ 128.4 257.6	GRAND RAPIDS TOWER★ 135.65 (CTAF) 0 339.8	GND CON 121.8	UNICOM 122.95
------------------------	--	---	-------------------------	-------------------------

MISSED APCH FIX

EC-1, 09 JUL 2026 to 06 AUG 2026

ELEV 794 **D** TDZE 790

MIRL Rwy 8L-26L **L**
REIL Rwy 8L, 17 and 26R **L**
HIRL Rwy 8R-26L and 17-35 **L**

2700	FERLI	tr 267°	JAKES	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73).							
				DAXEJ 2.5 NM to RW26L	CAVUS 2700	HAPIG					
* LNAV only.				* 1.3 NM to RW26L	* 1640	2700	GP 3.00° TCH 55				
				1.3 NM	1.2 NM	3.2 NM	6.1 NM				
CATEGORY	A		B		C		D				
LPV DA **	990/24 200 (200-½)										
LNAV/VNAV DA	1114/24 324 (400-½)						1114/40 324 (400-¾)				
LNAV MDA	1280/24 490 (500-½)		1280/40 490 (500-¾)		1280/50 490 (500-1)						
CIRCLING	1280-1 486 (500-1)		1340-1½ 546 (600-1½)		1360-2 566 (600-2)						

GRAND RAPIDS, MICHIGAN
Amdt 1C 29MAR18

42°53'N-85°31'W

GERALD R FORD INTL (G.R.R)

RNAV (GPS) RWY 26L

EC-1, 09 JUL 2026 to 06 AUG 2026