

|         |          |       |
|---------|----------|-------|
| APP CRS | Rwy Ldg  | 10000 |
| 087°    | TDZE     | 91    |
|         | Apt Elev | 96    |

RNAV (RNP) Y RWY 9

GEORGE BUSH INTCNL/HOUSTON (IAH)

▼

For uncompensated Baro-VNAV systems, procedure NA below -3°C (27°F) or above 54°C (130°F). GPS required. For inop MALSR, increase all Cats visibility to 1½ mile. Simultaneous approach authorized. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSR

AS

MISSED APPROACH: Climb to 580 then climbing right turn to 3000 direct JEBOX and hold.

|                  |                                                      |                               |                    |
|------------------|------------------------------------------------------|-------------------------------|--------------------|
| D-ATIS<br>124.05 | HOUSTON APP CON<br>120.05 379.1 E<br>124.35 316.15 W | HOUSTON TOWER<br>135.15 290.2 | GND CON<br>118.575 |
|------------------|------------------------------------------------------|-------------------------------|--------------------|

ELEV 96

TDZE 91

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).

580

3000

JEBOX

SAYNO

HYWAY

GP 3.00° TCH 50

3000

2000

2000

4.7 NM

5.8 NM

RWY 09

|             |                    |   |   |   |
|-------------|--------------------|---|---|---|
| CATEGORY    | A                  | B | C | D |
| RNP 0.30 DA | 516/49 425 (500-1) |   |   |   |

AUTHORIZATION REQUIRED

9000 X 150

9402 X 150

2001 X 150

1000 X 150

10000 X 150

26L

26R

27

33L

33R

TWR

TDZ/CL Rwy's 8R, 8L, 15R, 26R, 26L, 27 and 33L  
HIRL all Rwy's

HOUSTON, TEXAS  
Orig-B 13SEP18

29°59'N-95°20'W

GEORGE BUSH INTCNL/HOUSTON (IAH)

RNAV (RNP) Y RWY 9

SC-5, 09 JUL 2026 to 06 AUG 2026

SC-5, 09 JUL 2026 to 06 AUG 2026