

WAAS
CH **72926**
W09A

APP CRS
087°

Rwy Ldg **10000**
TDZE **91**
Apt Elev **96**

RNAV (GPS) Z RWY 9

GEORGE BUSH INTCNL/HOUSTON (IAH)

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -3°C (27°F) or above 54°C (130°F). For inop MALSR, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV Cat E visibility to 1½ mile, and LNAV Cat C/D/E visibility to 1¾ mile. Simultaneous approach authorized with Rwy 8L/R. DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.
** RVR 1800 authorized with use of FD or AP or HUD to DA.


MALSR



MISSED APPROACH: Climb to 580 then climbing right turn to 3000 direct JEBOX and hold.

D-ATIS 124.05	HOUSTON APP CON 120.05 379.1 E 124.35 316.15 W	HOUSTON TOWER 135.15 290.2	GND CON 118.575
-------------------------	--	--------------------------------------	---------------------------

RADAR REQUIRED



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).

URANG CHILT MEDIC DOHNN SAYNO HYWAY RWY09

5000 5000 4000 4000 3000 2000 2000

GP 3.00° TCH 50

5 NM 4.3 NM 3.8 NM 3.9 NM 4.7 NM 4.5 NM 1.3


580 3000 JEBOX

*LNAV only.

*1.3 NM to RWY09

CATEGORY	A	B	C	D	E
LPV DA**	291/24		200 (200-½)		
LNAV/VNAV DA	525/50		434 (500-1)		
LNAV MDA	580/24	489 (500-½)	580/50	489 (500-1)	

ELEV 96 TDZE 91



TDZ/CL Rwy's 8R, 8L, 15R, 26R, 26L, 27 and 33L
HIRL all Rwy's

HOUSTON, TEXAS
Amdt 5B 07DEC17

GEORGE BUSH INTCNL/HOUSTON (IAH)
29°59'N-95°20'W

RNAV (GPS) Z RWY 9