

FORT DRUM, NEW YORK

ILS or LOC RWY 3

LOC/DME I-AEZ

108.5

Chan 22

APCH CRS

029°

Rwy Idg

8631

TDZE

685

Arpt Elev

690

[USA]

WHEELER-SACK AAF (FORT DRUM) (KGTB)

DME or RADAR required. RADAR required for procedure entry.

ALSF-1

MISSED APPROACH: Climb to 1200, then climbing left turn to 5000 direct ART VORTAC and hold. Continue climb-in-hold to 5000.

ATIS

119.525

APP CON

124.875 307.125

TOWER

118.75 290.25

GND CON

123.65 229.8

ASR/PAR

*** When ALS inop, increase vis to ¾ mile;
CAT C vis to 1 ¼ miles; CAT D vis to 1 ¼ miles;
CAT E vis to 1 ½ miles.

*** Circling NA E of Rwy 21 and 33.
Circling NA for CAT BCD to Rwy 8.
Circling NA for CAT E to Rwy 8-26 and 15-33.

LOCALIZER 108.5

I-AEZ

Chan 22

WATERTOWN

109.8 ART

Chan 35

2511

Λ

2572

Λ

2041

2500

3600

260°

010°

JOGIN

I-AEZ 18

RADAR

KIMBO

I-AEZ 8.3

RADAR

REMIC

I-AEZ 4.3

RADAR

I-AEZ 2.6

RADAR

I-AEZ 1.6

RADAR

1200

5000

ART

GS 3.00°

TCH 66

5000

3000

2992

1560

4.2 NM

2.7 NM

CATEGORY	A	B	C	D	E
S-ILS 3 *	957-1 ½		272	(300-1 ½)	
S-LOC 3 **	1560-1 ½ 875 (900-1 ½)	1560-¾ 875 (900-¾)	1560-2 875 (900-2)	1560-2 ¼ 875 (900-2 ¼)	1560-2 ½ 875 (900-2 ½)
CIRCLING	1560-1 ¼ 870 (900-1 ¼)		1560-2 ½ 870 (900-2 ½)	1560-2 ¾ 870 (900-2 ¾)	1640-3 950 (1000-3)
DME MINIMUMS					
S-LOC 3 ***	1080-1 ½ 395 (400-1 ½)		1080-¾ 395 (400-¾)	1080-1 395 (400-1)	
CIRCLING	1200-1 510 (600-1)		1220-1 ½ 530 (600-1 ½)	1380-2 ¼ 690 (700-2 ¼)	1640-3 950 (1000-3)

FAF to MAP 6.9 NM

Knots

60 90 120 150 180

Min:Sec

6:54 4:36 3:27 2:46 2:18

NE-2, 09 JUL 2026 to 06 AUG 2026

NE-2, 09 JUL 2026 to 06 AUG 2026

FORT DRUM, NEW YORK

44° 03'N-75° 43'W

WHEELER-SACK AAF (FORT DRUM) (KGTB)

Amtd 3 23MAR23

ILS or LOC RWY 3