

WAAS CH 45805 W35B	APP CRS 356°	Rwy Ldg 13400 TDZE 564 Apt Elev 607	RNAV (GPS) RWY 35L DALLAS-FORT WORTH INTL (DFW)
--	------------------------	--	---

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C (25°F) or above 54°C (130°F). Simultaneous approach authorized with Rwy 36L/R and Rwy 35R.
DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSR

MISSED APPROACH:

Climb to 3000 direct BBAKR and on track 357° to BOSSI and hold.

D-ATIS 123.775	LONE STAR APP CON 127.075	DFW TOWER 126.55 127.5 (E) 124.15 134.9 (W)	GND CON 121.65 121.8 (E) 121.85 (W)
--------------------------	-------------------------------------	---	---

RADAR REQUIRED

GP 3.00°
TCH 47

6000

5000

3000

2300

TANDL

CORMN

DALLN

BEGGO

BBAKR

BOSSI

3.2 NM

6.3 NM

2.4 NM

4.1 NM

1.2

DA

764/18

200 (200-½)

DA

928/40

364 (400-¾)

MDA

1020/24

456 (500-½)

1020/45

456 (500-¾)

ELEV 607

TDZE 564

DALLAS-FORT WORTH, TEXAS

Amcl 2B 17AUG17

32°54'N-97°02'W

DALLAS-FORT WORTH INTL (DFW)

RNAV (GPS) RWY 35L