


LOC I-DKX	APP CRS	Rwy Ldg	3499
111.3	260°	TDZE	832
		Apt Elev	833

LOC RWY 26

KNOXVILLE DOWNTOWN ISLAND (DKX)

DME required. RADAR required for procedure entry.		MISSED APPROACH: Climb to 4000 on heading 250° and on VXV VORTAC R-265 to SWASO/VXV 18 DME and hold.	
▼	Rwy 26 helicopter visibility reduction below ¾ SM NA.		
AWOS-3 125.375		KNOXVILLE APP CON 123.9 353.6	CLNC DEL 121.7
		UNICOM 123.075 (CTAF) 1	



4000 hdg 250°		VXV R-265	SWASO △	SPROC VXV 15 RADAR	
WOGEL INT RADAR		RIZEN OM RADAR		3500	
3.38° TCH 44		2700		260°	
1520		3 NM		2.1 NM	
				7.4 NM	
CATEGORY	A	B	C	D	
S-26	1520-1 688 (700-1)		1520-2 688 (700-2)	NA	
CIRCLING	1600-1 767 (800-1)	1720-1¼ 887 (900-1¼)	1720-2¾ 887 (900-2¾)	NA	
WOGEL FIX MINIMUMS					
S-26	1440-1 608 (700-1)		1440-1¾ 608 (700-1¾)	NA	
CIRCLING	1600-1 767 (800-1)	1720-1¼ 887 (900-1¼)	1720-2¾ 887 (900-2¾)	NA	

ELEV 833	TDZE 832
REIL Rwys 8 and 26 1	
MIRL Rwy 8-26 1	
FAF to MAP 5.1 NM	
Knots	60 90 120 150 180
Min:Seq	5:06 3:24 2:33 2:02 1:42