

WAAS CH 48905 W29A	APP CRS 291°	Rwy Ldg TDZE 1004 Apt Elev 1004
--	------------------------	---

RNAV (GPS) RWY 29

KANSAS CITY/LEE'S SUMMIT RGNL (LXT)


RNP APCH - GPS.

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. VDP and Baro-VNAV NA when using Kansas City Downtown/Wheeler Fld altimeter setting. When local altimeter setting not received, use Kansas City Downtown/Wheeler Fld altimeter setting: increase LPV DA to 1322 feet; increase LNAV/VNAV DA to 1359 feet; increase all MDA 80 feet and visibility Cats C and D ¼ SM.

MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 direct LYMES and hold.

ASOS 124.175	KANSAS CITY APP CON 118.4 307.35	UNICOM 122.8 (CTAF) 0
------------------------	--	---------------------------------



ELEV 1004 TDZE 1004

REIL Rws 11, 18, 29 and 36
MIRL Rws 11-29 and 18-36

	1500	3000	LYMES	
	↑	↻	△	
			ZEVED 1.7 NM to RW29	
			1 NM to RW29	
			291°	
			2600	
			1580	
			291°	
			2600	
			292°	
			112°	
			4 NM Holding Pattern	
			ZONKI	
			3100	
			GP 3.00° TCH 40	
CATEGORY	A	B	C	D
LPV DA		1254-1	250 (300-1)	
LNAV/VNAV DA		1291-1	287 (300-1)	
LNAV MDA		1360-1	356 (400-1)	
CIRCLING	1440-1 436 (500-1)	1540-1 536 (600-1)	1780-2¼ 776 (800-2¼)	1780-2½ 776 (800-2½)