

WAAS CH 82404 W28A	APP CRS 281°	Rwy Ldg TDZE Apt Elev	4001 928 928
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 28

MIDDLETON MUNI/MOREY FLD (C29)

RNP APCH - GPS.


▼

▲

Baro-VNAV NA. Helicopter visibility reduction below $\frac{3}{4}$ SM NA. When local altimeter setting not received, use Dane County Rgnl/Truax Fld altimeter setting. VDP NA when using Dane County Rgnl/Truax Fld altimeter setting. Circling NA to Rwy's 1 and 19.

MISSED APPROACH:
Climb to 4000 direct JALOX and hold.

AWOS-3 118.675	MADISON APP CON ★ 135.45 343.7	UNICOM 123.0 (CTAF) 📻
--------------------------	--	--



ELEV 928	TDZE 928
-----------------	-----------------

4000

JALOX

VGSI and RNAV glidepath not coincident (VGSI Angle 4.00/TCH 36).

EXIDE

Holding Pattern

GUZBY

281°

3500

CAVEX

2600

RW28

1.2 NM to RW28

1.2 NM

3.9 NM

3 NM

3 NM

GP 3.00°

TCH 40

CATEGORY	A	B	C	D
LPV DA	1326-1½		398 (400-1½)	NA
LNAV/VNAV DA	1442-1¾		514 (600-1¾)	NA
LNAV MDA	1480-1	552 (600-1)	1480-1½ 552 (600-1½)	NA
CIRCLING	1560-1 632 (700-1)	1640-1 712 (800-1)	1660-2 732 (800-2)	NA

MIRL Rwy 10-28 **📻**
REIL Rwy's 10 and 28 **📻**