

APP CRS
280°

Rwyt Ldg
TDZE
Apt Elev

3803
422
424

RNAV (GPS) RWY 28

WILLIAMSON/SODUS (SDC)

RNP APCH - GPS.

Procedure NA at night. Rwy 28 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Rochester altimeter setting and increase all MDAs 80 feet and LNAV visibility Cat C ¼ SM, and Circling visibility Cat C ¼ SM.

MISSED APPROACH:
Climb to 3000 direct GOYER and hold.

AWOS-3 124.2	ROCHESTER APP CON 119.55 269.6	UNICOM 122.8 (CTAF) 0
-----------------	-----------------------------------	--------------------------

The main chart displays the RNAV (GPS) RWY 28 approach. It includes the following elements:

- MOAs:** R-5203 and MISTY 2 MOA at the top; MISTY 3 MOA on the left.
- Waypoints and Altitudes:**
 - GOYER: 100° heading, 280° heading, 4 NM from start.
 - RW28: 715° heading, 280° heading, 2000' altitude.
 - JAKRR: 281° heading, 281° heading, 2000' altitude.
 - WALCO: 101° heading, 281° heading, 3100' altitude.
 - JORAX: 101° heading, 011° heading, 3200' and 3400' altitudes.
 - ZIKEM: 191° heading, 101° heading, 3100' altitude.
- Obstacles:** 3803 x 60' obstacle near RW28.
- Altitude Restrictions:** 30 NM to ZIKEM, 20 NM to JORAX, 30 NM to WALCO.
- Angles:** 101°, 191°, 280°, 281°, 011°, 295°.
- Distances:** 4 NM, 6 NM, 12 NM.

ELEV 424

TDZE 422

3000 GOYER

280°

10

3803 X 60

28

4.5 NM

6 NM

WALCO

JAKRR

RW28

280°

281°

101°

6000

3100

4 NM Holding Pattern

CATEGORY	A	B	C	D
LNAV MDA	980-1	558 (600-1)	980-1½ 558 (600-1½)	NA
CIRCLING	1000-1 576 (600-1)	1020-1 596 (600-1)	1120-2 696 (700-2)	NA

MIRL Rwy 10-28 0

REIL Rwy 10 and 28 0

WILLIAMSON/SODUS, NEW YORK

Amdt 2B 06OCT22

43°14'N-77°07'W

WILLIAMSON/SODUS (SDC)

RNAV (GPS) RWY 28