

WAAS CH 72917 W07A	APP CRS 074°	Rwy Ldg TDZE Apt Elev	7299 1460 1478
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 7R

PHOENIX DEER VALLEY (DVT)

RNP APCH - GPS.


▼

⚠

When VGSI inop, Circling Rwy 25R NA at night. When local altimeter setting not received, use Scottsdale altimeter setting: increase LPV DA to 1822 feet and all visibilities $\frac{1}{8}$ SM, increase LNAV/VNAV DA to 2160 feet and all visibilities $\frac{1}{8}$ SM, increase all MDAs 40 feet and increase Circling Cat B visibility $\frac{1}{4}$ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Baro VNAV and VDP NA when using Scottsdale altimeter setting. Circling NA north of Rwy 7R-25L at night.

MISSED APPROACH: Climb to 5000 direct VIFPE and track 069° to AVENT and hold, continue climb-in-hold to 5000.

ATIS 126.5	PHOENIX APP CON 120.7 239.0	DEER VALLEY TOWER ★ 118.4 (070°-250°) (CTAF) 120.2 (251°-069°)	GND CON 121.8	UNICOM 122.95
----------------------	---------------------------------------	--	-------------------------	-------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 46).

5000

VIFPE

tr 069°

AVENT

BOLES

CEGAP

JURUX 3 NM to RWY 7R

1.8 NM to RWY 7R

RWY 7R

GP 3.00° TCH 42

3900

2900

2440

6 NM

1.4 NM

1.2 NM

1.8 NM

CATEGORY

A

B

C

D

LPV DA

1795-1 $\frac{1}{8}$

335 (400-1 $\frac{1}{8}$)

LNAV/VNAV DA

2133-2 $\frac{1}{2}$

673 (700-2 $\frac{1}{2}$)

LNAV MDA

2060-1

600 (600-1)

2060-1 $\frac{3}{4}$

600 (600-1 $\frac{3}{4}$)

CIRCLING

2400-1 $\frac{1}{4}$
922 (1000-1 $\frac{1}{4}$)

2420-1 $\frac{1}{4}$
942 (1000-1 $\frac{1}{4}$)

2580-3
1102 (1200-3)

2700-3
1222 (1300-3)

MIRL Rwy 7L-25R and 7R-25L

REIL Rwy 7L, 7R, 25L, and 25R