

4 NM Holding Pattern		SUBME		CEDIK		REVSE		RW35		YASXU	
6000 3100		177° 357°		2200		1580		1.6 NM to RW35		*LNAV only.	
GP 3.00° TCH 40		6.1 NM		1.9 NM		0.6		1.6 NM			
CATEGORY	A	B	C	D							
LPV DA	1124-1	250 (300-1)		NA							
LNAV MDA	1400-1	526 (600-1)	1400-1½ 526 (600-1½)	NA							
CIRCLING	1520-1	646 (700-1)	1780-2¾ 906 (1000-2¾)	NA							

Diagram illustrating the final approach segment. The approach is a straight-in approach to RW35, starting from a 4 NM Holding Pattern at 3100 MSL. The approach is a 357° heading, with a 2200 MSL altitude. The distance from the holding pattern to CEDIK is 6.1 NM, and from CEDIK to REVSE is 1.9 NM. The distance from REVSE to RW35 is 0.6 NM. The distance from the start of the approach to RW35 is 1.6 NM. The approach is a 357° heading, with a 2200 MSL altitude. The distance from the start of the approach to RW35 is 1.6 NM. The approach is a 357° heading, with a 2200 MSL altitude. The distance from the start of the approach to RW35 is 1.6 NM.

Diagram illustrating the final approach segment. The approach is a straight-in approach to RW35, starting from a 4 NM Holding Pattern at 3100 MSL. The approach is a 357° heading, with a 2200 MSL altitude. The distance from the holding pattern to CEDIK is 6.1 NM, and from CEDIK to REVSE is 1.9 NM. The distance from REVSE to RW35 is 0.6 NM. The distance from the start of the approach to RW35 is 1.6 NM. The approach is a 357° heading, with a 2200 MSL altitude. The distance from the start of the approach to RW35 is 1.6 NM. The approach is a 357° heading, with a 2200 MSL altitude. The distance from the start of the approach to RW35 is 1.6 NM.