

LOC/DME I-IPJ

111.15

Chan 48(Y)

APP CRS

233°

Rwy Ldg

5501

TDZE

872

Apt Elev

878

ILS Y or LOC Y RWY 23

LINCOLN COUNTY RGNL (IPJ)

RNP APCH - GPS.

VDP NA when using CLT altimeter setting. Rwy 23 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use CLT altimeter setting: increase S-ILS 23 DA to 1213 feet and visibilities ½ SM; increase all MDAs 80 feet and S-LOC 23 visibility Cats C/D ½ SM and Circling visibility Cats C/D ¼ SM; increase GATEQ Fix Minimums S-LOC visibility Cats C/D and Circling visibility Cats C/D ¼ SM.

MISSED APPROACH: Climb to 1600 then climbing right turn to 3100 direct JIVOM and hold.

AWOS-3 119.675	CHARLOTTE APP CON 134.75 257.2	CLNC DEL (GCO) 124.9	UNICOM 123.05 (CTAF) ①
-------------------	-----------------------------------	-------------------------	---------------------------

ELEV 878

TDZE 872

1600

3100

JIVOM HPJ 13.4

233°

0.3% UP

5700 X 100

REIL Rws 5 and 23 ①

MIRL Rwy 5-23 ①

1600

3100

JIVOM HPJ 13.4

CISBU INT HPJ 6 RADAR

GATEQ HPJ 3

HPJ 2.2

HPJ 1

2500

1460

2500

1.2 NM

0.9

3 NM

7.4 NM

4 NM Holding Pattern

053°

233°

6000

3000

GS 3.00°

TCH 47

CATEGORY	A	B	C	D
S-ILS 23	1149-7/8 277 (300-7/8)			
S-LOC 23	1460-1	588 (600-1)	1460-1¾ 588 (600-1¾)	1660-2½ 782 (800-2½)
CIRCLING	1460-1	582 (600-1)	1660-2½ 782 (800-2½)	1660-2½ 782 (800-2½)

GATEQ FIX MINIMUMS

S-LOC 23	1280-1	408 (500-1)	1280-1½ 408 (500-1½)	
CIRCLING	1400-1	522 (600-1)	1440-1	562 (600-1)

LINCOLNTON, NORTH CAROLINA

Orig-D 22JAN26

35°29'N-81°10'W

ILS Y or LOC Y RWY 23

SE-2, 09 JUL 2026 to 06 AUG 2026