


CHARLOTTE DEP CON
134.75 257.2
AWOS-3
119.675
CLNC DEL (GCO)
124.9

RNAV 1 - DME/DME/IRU or GPS.
RADAR required.

TOP ALTITUDE:
3000

TAKEOFF MINIMUMS
Rwys 5, 23: Standard.




NOTE: Turbojet only.
NOTE: If unable to accept climb rates, advise ATC on initial contact.
NOTE: Transponder code will be issued via PDC or CLT CLNC DEL.
NOTE: Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable advise ATC.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 5: Climb on heading 063° to 2000 before proceeding on course, then on heading assigned by ATC, thence. . .
TAKEOFF RUNWAY 23: Climb on heading 243° to 2800 before turning left, then on heading assigned by ATC, thence. . .
...for RADAR vectors to WAYDS, then on depicted route to JOJJO. Then on assigned transition.
Maintain 3000, expect filed altitude 10 minutes after departure.

CUBIM TRANSITION (JOJJO7.CUBIM)
DOOGE TRANSITION (JOJJO7.DOOGE)
NOONN TRANSITION (JOJJO7.NOONN)



NOTE: Chart not to scale.