

WAAS CH 99307 W16A	APP CRS 173°	Rwy Ldg 12000 TDZE 5357 Apt Elev 5434
--	------------------------	--

RNAV (GPS) Y RWY 16L

DENVER INTL (DEN)


RNP APCH - GPS.

Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -26°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility, and LNAV Cats C/D visibility to RVR 4500.

MALSR

MISSED APPROACH: Climb to 10000 direct SUGOY and on track 202° to SIGNE and hold.

D-ATIS 125.6 379.9	DENVER APP CON 119.3 307.3 (N) 120.35 379.3 (S)	DENVER TOWER 135.3 351.95	GND CON 121.35 379.175 (W) 121.85 377.1 (E)
------------------------------	---	-------------------------------------	---



10000	SUGOY	tr 202°	SIGNE	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00°/TCH 71°).			
↑			△		KUURT	JOBOB	JEEPR
				LUWEE 1.3 NM to RW16L	KIKME	10000	10000
				0.8 NM to RW16L	LEETS	7000	9000
				5820	7000	8000	10000
				0.8	0.6	3.7 NM	3.2 NM
				B			
				C			
				D			
CATEGORY							
LPV DA				5557/18 200 (200-½)			
LNAV/VNAV DA				5647/24 290 (300-½)			
LNAV MDA				5660/24 303 (300-½)			

ELEV 5434

D

TDZE 5357

HIRL all Rwys

TDZL/RCLS Rwys 7, 16L, 16R, 17R, 26, 34L, 34R, 35L, 35R