


WAAS CH 62825 W23A	APP CRS 227°	Rwy Ldg TDZE 352 Apt Elev 368
--	------------------------	---

RNAV (GPS) RWY 23
TRIANGLE NORTH EXEC (LHZ)


⚠ Baro-VNAV NA when using Raleigh-Durham altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 41°C (105°F). When VGSi inop, Straight-in/Circling Rwy 23 procedure NA at night. DME/DME RNP-0.3 NA. Helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Raleigh-Durham altimeter setting and increase LPV DA to 667 feet; LNAV/VNAV DA to 684 feet and all visibilities ½ SM. Increase all MDAs 80 feet and visibility Cats C/D ¾ SM.

MISSED APPROACH: Climb to 3300 direct ERUYO and on track 198° to ZEBUL and hold, continue climb-in-hold to 3300.

AWOS-3 118.325	RALEIGH APP CON 125.3 353.675	UNICOM 123.0 (CTAF) 0
--------------------------	---	---------------------------------



3300	ERUYO	tr 198°	ZEBUL				
							
* LNAV only				COGBO 1.7 NM to RW23			
							
							
1.7 NM				3.7 NM		8.5 NM	
				JOPOT 2100			
					227°	2100	
				JIPSI			
					2600		GP 3.00° TCH 46
CATEGORY		A		B		C	D
LPV DA				602-1		250 (300-1)	
LNAV/ VNAV DA				619-1		267 (300-1)	
LNAV MDA				700-1		348 (400-1)	
CIRCLING	800-1 432 (500-1)		840-1 472 (500-1)		980-1¾ 612 (700-1¾)		1000-2 632 (700-2)



SE-2, 09 JUL 2026 to 06 AUG 2026

SE-2, 09 JUL 2026 to 06 AUG 2026