

WAAS CH 90103 W05A	APP CRS 046°	Rwy Ldg 5498 TDZE 368 Apt Elev 368
--	------------------------	---

RNAV (GPS) RWY 5
TRIANGLE NORTH EXEC (LHZ)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 41°C (105°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Raleigh-Durham altitude setting and increase LPV DA to 633 feet; LNAV/VNAV DA to 705 feet and all visibilities ½ SM. Increase all MDAs 80 feet and visibility Cat C/D ¼ SM. For inop MALS, increase LNAV/VNAV all Cats visibility to ½ mile and LNAV Cats C/D visibility to 1 mile. For inop MALS when using Raleigh-Durham altimeter setting, increase LPV all Cats visibility to ½ mile. Baro-VNAV and VDP NA with Raleigh-Durham altimeter setting.

MALSR





MISSED APPROACH:
Climb to 2600 direct
JPSI and hold.

AWOS-3
118.325

RALEIGH APP CON
125.3 353.675

UNICOM
123.0 (CTAF) **L**



CATEGORY	A	B	C	D
LPV DA	568- ¹ / ₂ 200 (200- ¹ / ₂)			
LNAV/VNAV DA	640- ¹ / ₂ 272 (300- ¹ / ₂)			
LNAV MDA	740- ¹ / ₂ 372 (400- ¹ / ₂)		740- ⁵ / ₈ 372 (400- ⁵ / ₈)	
CIRCLING	800-1 432 (500-1)	840-1 472 (500-1)	980- ¹³ / ₄ 612 (700- ¹³ / ₄)	1000-2 632 (700-2)

