

WAAS
CH **86939**
W36A

APP CRS
002°

Rwy Ldg
TDZE
Apt Elev

4244
3124
3124

RNAV (GPS) RWY 36

CITY OF SLATON/LARRY T NEAL MEML (F49)

Baro-VNAV NA. DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 5300 direct JONON and hold.

LBB ASOS
125.3 270.275

LUBBOCK APP CON
119.2 351.8

UNICOM
123.0 (CTAF) 0

Procedure NA for arrivals on LBB VORTAC airway radials 075 CW 216.

LUBBOCK LBB

5000
147°
(6.8)

MISSED APCH FIX

4 NM
002°
182°
JONON

MSA RW 36 2.5 NM

5200

5000 NoPT
047°
(5)

(IF/IAF) TAGAE
(RADAR required)

4700
002°
(6.1)

(IF/IAF) HAXEB

4700
002°
(6.1)

5000 NoPT
317°
(5)

(IAF) WATUS
(RADAR REQD)

3456
002°
(6.1)

(FAF) CAGOX

RW36

4 NM Holding Pattern

5000
182°
002°

GP 3.00° TCH 40

HAXEB

4700

CAGOX

4700

RW36

6.1 NM

4.9 NM

5300 JONON

81
4244 X 75
3175

36
002°

MIRL Rwy 18-36 0

CATEGORY	A	B	C	D
LPV DA		3883-3	759 (800-3)	
LNAV/VNAV DA		3849-3	725 (800-3)	
LNAV MDA	3760-1	636 (700-1)	3760-1¾	636 (700-1¾)
CIRCLING	3760-1 636 (700-1)	3820-1 696 (700-1)	3820-2 696 (700-2)	3820-2¼ 696 (700-2¼)

SLATON, TEXAS

CITY OF SLATON/LARRY T NEAL MEML (F49)

Orig 05JAN17

33°29'N-101°40'W

RNAV (GPS) RWY 36